

HEAVY DUTY

SOFO

CONCENTRATED

**SOLVENT
DEGREASER**

CAUTION

KEEP OUT OF REACH OF CHILDREN

HARMFUL IF SWALLOWED. COMBUSTIBLE. CONTAINS ALIPHATIC SOLVENTS. AVOID CONTACT WITH SKIN, EYES, CLOTHING AND AVOID BREATHING SPRAY MIST. DO NOT USE IN A POORLY VENTILATED AREA OR IN PRESENCE OF SPARKS OR OPEN FLAME. USE PROTECTIVE GLOVES AND EYE SHIELD.

5 GALLONS

FOR INDUSTRIAL & INSTITUTIONAL USE ONLY

A heavy-duty, concentrated, emulsifiable solvent degreaser. Because of its rapid action, deep penetrating activity, and its ability to be flushed clean with water, the removal of stubborn soils such as grease, oils, dirt, waxes, tar and asphalt are made easy. This product may be used as a spray on-flush off degreaser, immersion tank cleaner, or to degrease heavily soiled concrete floors. Excellent for use on automobiles, trucks, tractors, farm and construction equipment, tar and asphalt machinery, motors, filters and metal parts. Dilute with kerosene, diesel fuel or petroleum solvents.

DIRECTIONS

CONCRETE FLOORS, AUTO ENGINES, ROAD AND FARM MACHINERY- Dilute 1 part product with 4-8 parts of solvent. Spray surface to be cleaned. Can be applied to floors by mopping or deck brush if very heavily soiled. Allow solution to penetrate for 10 minutes. Pressure hose clean.

MOTORS AND BLOCK TANK DIP- Use undiluted or dilute with 1 part solvent. Immerse object in dip tank. Soak until grease softens. Remove and pressure hose clean.

SMALL PITS- Submerge small parts in 1 part product diluted with 4 -8 parts solvent. Let soak for 10-20 minutes. Agitate stubborn grease with stiff brush. Remove and rinse with clear water.

FIRST AID

EYES- Flush with large amounts of water for 15 minutes. **SKIN CONTACT-** Flush thoroughly with large amounts of water. **INTERNAL- DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.**

INGREDIENTS: Aliphatic Hydrocarbon CAS # N/A, Isopropylamine Sulfonate CAS #68584-24-7, Tetrachloroethylene CAS #127-18-4

LICO INC.

929 FIFTH AVENUE
McKEESPORT, PA 15132
(412) 422-7786