

DIELECTRIC CONSTANT OVER  
25,000 VOLT, 500 ppm M.A.C.

# Solute

NON-CONDUCTIVE  
SAFETY SOLVENT  
DEGREASER

## WARNING

KEEP OUT OF REACH OF CHILDREN

**COMBUSTIBLE. HARMFUL IF SWALLOWED.  
CONTAINS CHLORINATED HYDROCARBONS.**

IF SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. USE IN WELL VENTILATED AREA. AVOID PROLONGED CONTACT WITH SKIN. WEAR RUBBER GLOVES. DO NOT USE NEAR SPARKS OR OPEN FLAME.

5 GALLONS

## FOR INDUSTRIAL & INSTITUTIONAL USE ONLY

A non-conductive safety solvent degreaser that cleans, de-greases, de-oils and de-waxes bare or painted metals. A corrosion free solvent that leaves no residue. Excellent for electrical controls, relays, contact points, machine motors, printing rollers, refrigerating systems, televisions, typewriters, bowling alleys, etc... Dielectric constant over 25,000 volts, 500 ppm M.A.C.

## DIRECTIONS

**IN-PLACE CLEANING-** Spray cold motors with enough of this product so that oil, grease, dirt, carbon and debris will flow out from the force of the spray. Run motor intermittently so as not to heat the motor. Blow motor dry with compressed air. **DO NOT USE ON D.C. MOTORS OR ARCING BRUSHES.**

**IMMERSION CLEANING-** Immerse small, cold electric motors in this product. Run for 3-6 minutes. Remove from solution and wipe or blow dry with compressed air.

This product may also be applied by brush, cloth or air-less equipment.

**BE SURE TO RE-LUBRICATE CLEANED MOTORS.**

INGREDIENTS: Hydrocarbon Solvent CAS #64742-88-7, Dichloromethane CAS #75-09-2, Tetrachloroethylene CAS #127-18-4

**LICO** INC.

929 FIFTH AVENUE • McKEESPORT, PA 15132  
(412) 422-7786