

STONE AGE

High Gloss Finish & Sealer
For Non-Resilient Floors

1 GALLON

See side panel for additional cautions and first aid statement.
CAUTION: Keep out of reach of children.

STONE AGE - A high gloss finish & sealer for non-resilient floors.

Revolutionizes the maintenance and care of non-resilient floors. This sealer is formulated specifically for use on floor surfaces such as: VCT, terrazzo, ceramic tile, terra cotta, slate, granite, marble, concrete, quarry tile and other natural stone floors. Adheres to these natural stone or mineral surfaces with polymer technology, eliminating poor adhesion problems. Provides the ultimate in gloss and protection to worn or dull floors while protecting against chemical spills and traffic. STONE AGE has great water resistance and seals and finishes surfaces in one step. STONE AGE works well as a versatile performing product from low infrequent maintenance to high frequency maintenance floor programs.

DIRECTIONS

1. Clean and/or strip floor. Make sure that if a floor stripper is used that it is safe to use on the natural stone or mineral type of surface, sometime these types of floors may be damaged by extreme pH levels found in some floor strippers.
2. Rinse surfaces *thoroughly* with clear water.
3. **Allow 2 to 3 hours of drying time for moisture to evaporate out of stone surface before applying sealer.**
4. Apply thin coats of STONE AGE using a mop or floor finish applicator. Allow 30 to 40 minutes dry time between coats. Note: NEW Terrazzo floors may need to be neutralized with a mild acid solution before they will accept the coating.
5. Two to Four coats may be required to attain desired gloss.
6. May buff product, exercise care while buffing due to unevenness of stone floors.

CAUTION

Keep out of reach of children. Do not take internally. Harmful if swallowed. Avoid contact with eyes.

FIRST AID

If swallowed, drink plenty of water. Do not induce vomiting. Contact a physician immediately. If in eyes, flush with large amounts of water for 15 minutes, lifting upper and lower lids occasionally. If irritation persists, contact a physician.

INGREDIENTS: Water CAS# 7732-18-5, DEG Methyl Ether CAS# 111-77-3, Tributoxyethyl Phosphate CAS# 78-51-3, Zinc Ammonium Carbonate CAS# 38714-47-5, Dibutyl Phthalate CAS# 84-74-2

LICO INC.

929 FIFTH AVENUE • McKEESPORT, PA 15132

Phone: 1-412-422-7786 or 1-412-664-4888 • Fax: 1-412-664-0940

E Mail: savemore@Licochem.com

PRODUCT REORDER #L139