

# TUFF KOTE 151

**FLOOR FINISH**

**CAUTION**

**KEEP OUT OF REACH OF CHILDREN**

**1 GALLON**

A high solids, metallic interlocked floor finish which protects flooring and resists damage and dulling due to water, soaps and detergents. It is a self-polishing floor finish and does not need to be buffed. It can be cleaned repeatedly without dulling its shine. Finish can easily be removed from the floor by using a floor stripper.

Easy to apply and maintain due to the products incredibly low dirt retention. It is an extremely hard and durable floor finish with excellent gloss, black heel mark and slip resistance, and excellent patching qualities. Two coats of this finish is equal to three coats of a standard floor finish.

Excellent for use in a high traffic or abuse areas such as hospitals, office buildings, lobbies, supermarkets, hallways, schools, cafeterias, industrial plants, etc... Can be applied on vinyl, vinyl asbestos, rubber and asphalt tile.

## **DIRECTIONS**

Floors should be thoroughly stripped or cleaned as needed. Rinse and neutralize the floor and allow to dry. Apply a few this coats of floor finish, allowing each coat to dry before applying the next coat. Apply with a clean mop or lambswool applicator. Best results are obtained when applying thin coats which are crisscrossed rather than one thick coat.

Do not contaminate fresh floor finish with used material.

Do not allow finish to freeze.

**INGREDIENTS:** Glycol Ether CAS# 111-90-0, Dimethyl Carbinol CAS# 67-63-0, Dibutyl Phthalate CAS# 84-74-2, Acrylic Copolymer CAS# 25035-68

**LICO**  **INC.**

929 Fifth Avenue • McKeesport, PA 15132  
Phone: 1-800-560-9590 or 412-422-7786 Fax: 412-664-0940  
[www.Licochem.com](http://www.Licochem.com)