

5 GALLONS

# ULTRA 22

## FLOOR FINISH

METALLIC INTERLOCK THERMOPLASTIC

CAUTION: KEEP OUT OF REACH OF CHILDREN

A new breakthrough in thermoplastic polymer technology. A high solids, metallic interlocked polymer floor finish which protects flooring and resists damage and dulling due to water, soaps and detergents. Its unique characteristics make this product quite durable in non-buffable situations, but its thermoplasticity enables it to be high speed buffed to a brilliant gloss. It is extremely slip resistant and has excellent patching qualities.

Excellent for use in any high traffic areas such as hospitals, office buildings, lobbies, supermarkets, hallways, schools, cafeterias, industrial plant, etc.

Can be applied on vinyl asbestos, vinyl, rubber and asphalt tile and terrazzo surfaces.

### DIRECTIONS

- Floors should be thoroughly stripped or cleaned as needed.
- Rinse and neutralize the floor and allow to dry.
- Apply a few coats of floor finish, allowing each thin coat to dry before applying the next coat. Apply with a clean mop or lamb's wool applicator. Best results are obtained when applying thin coats which are crisscrossed, rather than applying one thick coat. DO NOT contaminate fresh floor finish with used materials. DO NOT allow floor finish to freeze.

**INGREDIENTS:**  
Glycol Ether CAS #111-90-0, Dimethyl Carbinol CAS #67-63-0, Dibutyl Phthalate CAS #64-74-2, Acrylic Copolymer CAS #62180-77-2.

**CAUTION: KEEP OUT OF REACH OF CHILDREN**

LICO<sub>INC</sub>

929 FIFTH AVENUE • McKEESPORT, PA 15132  
(412) 422-7786 • Fax (412) 664 - 0940