

5 GALLONS

# WATERLESS CLEANER & FLOOR PREP

**CAUTION**  
**KEEP OUT OF REACH OF CHILDREN**

**LICO INC.** 929 FIFTH AVENUE  
McKEESPORT, PA 15132  
(412) 422-7786 OR 664-4888

This product is designed for use on wood floors and surfaces where water would harm these surfaces. This cleaner will remove dirt and spills without harming the surface. It can also be used to remove rubber burns, black heel marks and other hard to remove items from the surface.

#### DIRECTIONS:

Coverage applied by wet mop and no rinse. 350 sq. ft. per gallon.

**As cleaner only on sealed floors:** Damp mop floors with waterless cleaner. Use the heel of the mop on stubborn spots and damp rinse the floor with a clean mop and waterless cleaner.

Rubber burns, black marks, etc. May be removed with a cloth dampened with waterless cleaner. Waterless Cleaner will soften gum so that it may be removed with a putty knife.

**Preparing sealed floors for recoating:** Clean away soluble soil (food or sugar) by damp mopping or wet scrubbing and allow to dry. Care must be taken to not warp the floor by allowing water to penetrate into the wood. To abrade the floor for good intercoat adhesion and to remove black marks, etc..., wet mop waterless cleaner onto floor 3-4 minutes ahead of a black stripping pad under a rotary machine. Move machine at the pace of a slow walk in full head passes overlapping 1-2 inches, tack rag with waterless cleaner to remove dust residues.

**New sanded or full stripped floors:** If chemically stripped, scrub with waterless cleaner to remove stripper residue and pick-up soiled solution with wet vacuum or mop.

#### CAUTION:

This material is combustible and will burn at high temperatures; therefore, use workman-like precautions against open flames or smoking in the area of use and be alert so that rags, mops and other absorbant materials that have been soaked with the product are properly cleaned and disposed of after use.

#### DANGER:

Harmful or fatal if swallowed. Combustible.  
Contains mineral spirits. Keep away from heat and open flames. Avoid prolonged contact with skin and breathing of vapors or spray mist. Use with adequate ventilation. Do not take internally, close container after each use. In case of spillage, absorb or dispose of in accordance with local regulations.

INGREDIENTS: Hydrocarbon Solvent CAS #64742-88-7