

# ***ACRYLIC BASE***

---

# **X-18**

---

# **FLOOR SEAL**

**CAUTION**

**KEEP OUT OF REACH OF CHILDREN**

**1 GALLON**

## **ACRYLIC BASE FLOOR SEAL**

A non-yellowing, acrylic based floor sealer for use on all porous resilient floors. It produces a complete bond with the floor, soaking into every crevice and fills pores until a thin film covers the entire surface. It provides a flexible protective coating which will accept floor finish coats without separating or streaking. Seals the floor surface so that moisture, dirt, grease, and oils cannot penetrate and damage or stain it.

This durable seal contains no solvents and is non-toxic and non-flammable. Protects new floors and will restore the original beauty and color to older worn floors. Floor finishes will yield higher coverage reducing materials costs.

Excellent for use in any high traffic or abuse areas such as hospitals, office buildings, lobbies, supermarkets, hallways, schools, cafeterias, etc... Can be applied on all resilient tile and even terrazzo and marble.

**DIRECTIONS:** Floors should be thoroughly stripped as needed. Rinse and neutralize the floor and allow to dry. Apply a thin coat of sealer, allowing enough time to dry before applying the second coat. Apply with a clean mop or lambswool applicator. Best results are obtained when applying thin coats which are criss-crossed rather than one thick coat.

**DO NOT** dilute, contaminate with used material, or allow to freeze.

INGREDIENTS: Glycol Ether CAS #11-77-3, Glycol Ether CAS #34590-94-8

**LICO INC.**

929 FIFTH AVENUE • McKEESPORT, PA 15132  
412/ 422-7786